



Product Service

CERTIFICATE

No. Z1A 094747 0049 Rev. 00

Holder of Certificate: **Xinsu Global Electronic Co., Limited**
Unit 2508A, 25/F Bank Of America Tower, 12 Harcourt Road
Central
HONG KONG

Certification Mark:



Product: **Switching power supply unit
(SWITCHING POWER SUPPLY/CHARGER)**

Tested according to: EN 62368-1:2014/A11:2017
AfPS GS 2019:01 PAK

The product meets the safety and health requirements of the German Product Safety Act section 20 to 22 ProdSG. The certification marks shown above can be affixed on the product. It is not permitted to alter the certification marks in any way. In addition, the certificate holder must not transfer the certificate to third parties. This certificate is valid until the listed date, unless it is cancelled earlier. All applicable requirements of the testing and certification regulations of TÜV SÜD Group have to be complied. For details see: www.tuvsud.com/ps-cert

Test report no.: 652102027201

Valid until: 2026-04-27

Date, 2021-04-28

(Rickyet Wang)

CERTIFICATE

No. Z1A 094747 0049 Rev. 00

Model(s):

XSGxxxxyyy, XSGxxxxyyyzz, XSExxxxyyy,
XSExxxxyyyzz, XSECxxxxyyy, XSECxxxxyyyzz
(xxx=036-588, which represent the rated output
voltage from 3.6VDC to 58.8VDC; yyy=0100-7000,
which represent the rated output current from 0.1A
to 7.0A; zz=AA-ZZ stands for marketing purpose, it
can be any two uppercase English letters.)

Brand Name:

Xinsu Global

**Parameters:**

Rated Input : 100-240VAC, 50/60Hz, 1.3A

Rated Output : See below table for details

Protection Class : II

Degree of Protection : IP20

CERTIFICATE

No. Z1A 094747 0049 Rev. 00

Model	Rated output voltage (VDC)	Rated output current (A)	Maximum rated output power (W)
XSGxxxxxyyyzz, XSGxxxxxyyy	3.6–5.0	0.1-7.0	35.0
	6.0–9.0	0.1-6.5	58.5
	10.0	0.1-6.0	60.0
	11.0	0.1-5.5	60.5
	12.0–12.6	0.1-5.0	63.0
	13.0–14.0	0.1-4.5	63.0
	14.6–15.0	0.1-4.0	60.0
	16.0	0.1-4.06	64.96
	16.8–17.0	0.1-3.75	63.75
	18.0–18.3	0.1-3.5	64.05
	19.0	0.1-3.42	64.98
	20.0	0.1-3.25	65.0
	21.0	0.1-3.0	63.0
	22.0	0.1-2.9	63.8
	22.5	0.1-2.89	65.025
	24.0	0.1-2.7	64.8
	25.2–25.5	0.1-2.5	63.75
	27.0	0.1-2.4	64.8
	28.0–29.0	0.1-2.1	60.9
	29.2–29.4	0.1-2.2	64.68
	30.0	0.1-2.0	60.0
	32.0	0.1-2.0	64.0
	33.0–34.0	0.1-1.9	64.6
	35.0–36.0	0.1-1.8	64.8
	36.5	0.1-1.75	63.875
	37.8	0.1-1.7	64.26
	38.0–43.0	0.1-1.5	64.5
	43.8–44.0	0.1-1.45	63.8
	45.0–46.2	0.1-1.4	64.68
	47.5–48.0	0.1-1.35	64.8
	50.4	0.1-1.25	63.0
	51.0–51.1	0.1-1.2	61.32
	54.6	0.1-1.15	62.79
	54.8–58.4	0.1-1.0	58.4
	58.8	0.1-1.1	64.68



CERTIFICATE

No. Z1A 094747 0049 Rev. 00

Model	Rated output voltage (VDC)	Rated output current (A)	Maximum rated output power (W)
XSExxxxxyzz, XSExxxxxy, XSECxxxxxyzz, XSECxxxxxy	3.6–5.0	0.1–7.0	35.0
	5.1–9.0	0.1-6.5	58.5
	10.0-12.0	0.1-6.0	60.0
	12.1–12.6	0.1-5.0	63.0
	12.8–15.0	0.1-4.5	65.0
	16.0–20.0	0.1-3.75	65.0
	21.0–30.0	0.1-3.0	65.0
	31.0–58.8	0.1-2.0	65.0