



Product Service

CERTIFICATE

No. Z1A 094747 0004 Rev. 02

Holder of Certificate: **Xinsu Global Electronic Co., Limited**
Unit 2508A, 25/F Bank Of America Tower, 12 Harcourt Road
Central
HONG KONG

Certification Mark:



Product: **Switching power supply unit
(SWITCHING POWER SUPPLY)**

Tested according to: EN IEC 61558-1:2019
EN 61558-2-16:2009/A1:2013
EN 60335-1:2012/A15:2021
EN 62233:2008
AfPS GS 2019:01 PAK

With this certificate, in its capacity as a notified GS body, TÜV SÜD Product Service GmbH issues the GS Mark to the named certificate holder for the declared product with the named model designation in accordance with section 20 ProdSG (German Product Safety Act). The product meets the safety and health requirements of section 20 (3) ProdSG. The manufacturer is reminded of their obligations in accordance with section 24 ProdSG. The certification marks shown above can be affixed on the product. It is not permitted to alter the certification marks in any way. In addition, the certificate holder must not transfer the certificate to third parties. This certificate is valid until the listed date, unless it is cancelled earlier. All applicable requirements of the testing and certification regulations of TÜV SÜD Group have to be complied. For details see: www.tuvsud.com/ps-cert

Test report no.: 652501602404

Valid until: 2028-06-13

Date, 2023-06-15


(Michael Xu)

CERTIFICATE

No. Z1A 094747 0004 Rev. 02

Model(s):

XSGxxxxxxx, XSGxxxxxxxzz, XSExxxxxxx,
XSExxxxxxxzz, XSECxxxxxxx, XSECxxxxxxxzz
(xxx=036-588, which represent the rated output
voltage from 3.6VDC to 58.8VDC; yyyy=0100-7000,
which represent the rated output current from 0.1A
to 7.0A; zz=AA-ZZ stands for marketing purpose, it
can be any two uppercase English letters.)

Brand Name:

Xinsu Global

**Parameters:**

Rated Input: 100-240VAC, 50/60Hz, 1.3A

Rated Output: See below table for details

Protection Class: II

Degree of Protection: IP20

CERTIFICATE

No. Z1A 094747 0004 Rev. 02

Model	Rated output voltage (VDC)	Rated output current (A)	Maximum rated output power (W)
XSGxxxxxyyyzz, XSGxxxxxyyy	3.6–5.0	0.1-7.0	35.0
	6.0–9.0	0.1-6.5	58.5
	10.0	0.1-6.0	60.0
	11.0	0.1-5.5	60.5
	12.0–12.6	0.1-5.0	63.0
	13.0–14.0	0.1-4.5	63.0
	14.6–15.0	0.1-4.0	60.0
	16.0	0.1-4.06	64.96
	16.8–17.0	0.1-3.75	63.75
	18.0–18.3	0.1-3.5	64.05
	19.0	0.1-3.42	64.98
	20.0	0.1-3.25	65.0
	21.0	0.1-3.0	63.0
	22.0	0.1-2.9	63.8
	22.5	0.1-2.89	65.025
	24.0	0.1-2.7	64.8
	25.2–25.5	0.1-2.5	63.75
	27.0	0.1-2.4	64.8
	28.0–29.0	0.1-2.1	60.9
	29.2–29.4	0.1-2.2	64.68
	30.0	0.1-2.0	60.0
	32.0	0.1-2.0	64.0
	33.0–34.0	0.1-1.9	64.6
	35.0–36.0	0.1-1.8	64.8
	36.5	0.1-1.75	63.875
	37.8	0.1-1.7	64.26
	38.0–43.0	0.1-1.5	64.5
	43.8–44.0	0.1-1.45	63.8
	45.0–46.2	0.1-1.4	64.68
	47.5–48.0	0.1-1.35	64.8
	50.4	0.1-1.25	63.0
	51.0–51.1	0.1-1.2	61.32
	54.6	0.1-1.15	62.79
	54.8–58.4	0.1-1.0	58.4
	58.8	0.1-1.1	64.68



CERTIFICATE

No. Z1A 094747 0004 Rev. 02

Model	Rated output voltage (VDC)	Rated output current (A)	Maximum rated output power (W)
XSExxxxxyzz, XSExxxxxy, XSECxxxxxyzz, XSECxxxxxy	3.6–5.0	0.1-7.0	35.0
	5.1–9.0	0.1-6.5	58.5
	10.0-12.0	0.1-6.0	60.0
	12.1–12.6	0.1-5.0	63.0
	12.8–15.0	0.1-4.5	65.0
	16.0–20.0	0.1-3.75	65.0
	21.0–30.0	0.1-3.0	65.0
	31.0–58.8	0.1-2.0	65.0