

No. N8AUK 094747 0153 Rev. 00

Holder of Attestation: Xinsu Global Electronic Co., Limited

Unit 2508A, 25/F Bank Of America Tower, 12 Harcourt Road

Central HONG KONG

Product: Switching power supply unit

(SWITCHING POWER SUPPLY)

This Attestation of Conformity is issued on a voluntary basis according to the Electrical Equipment (Safety) Regulations 2016 relating to electrical equipment designed for use within certain voltage limits. It confirms that the listed equipment complies with the principal protection requirements of the regulation and is based on the technical specifications applicable at the time of issuance. It refers only to the particular sample submitted for conformity assessment.

For details see: www.tuvsud.com/ps-cert

Test report no.: 652501602404

Date. 2023-06-14

(Michael Xu)

Page 1 of 4







No. N8AUK 094747 0153 Rev. 00

Model(s): XSGxxxyyyy, XSGxxxyyyyzz, XSExxxyyyy,

XSExxxyyyyzz, XSECxxxyyyy, XSECxxxyyyyzz (xxx=036-588, which represent the rated output voltage from 3.6VDC to 58.8VDC; yyyy=0100-7000, which represent the rated output current from 0.1A to 7.0A; zz=AA-ZZ stands for marketing purpose, it

can be any two uppercase English letters.)

Brand: Xinsu Global



Parameters:

Rated Input: 100-240VAC, 50/60Hz, 1.3A Rated Output: See below table for details

Protection Class: II
Degree of Protection: IP20

Tested EN IEC 61558-1:2019

according to: EN 61558-2-16:2009/A1:2013 EN 60335-1:2012/A15:2021

EN 62233:2008

BS EN IEC 61558-1:2019

BS EN 61558-2-16:2009/A1:2013 BS EN 60335-1:2012/A15:2021

BS EN 62233:2008









No. N8AUK 094747 0153 Rev. 00

Model	Rated output voltage (VDC)	Rated output current (A)	Maximum rated output power (W)
XSGxxxyyyy	3.6-5.0	0.1-7.0	35.0
	6.0-9.0	0.1-6.5	58.5
	10.0	0.1-6.0	60.0
	11.0	0.1-5.5	60.5
	12.0–12.6	0.1-5.0	63.0
	13.0–14.0	0.1-4.5	63.0
	14.6–15.0	0.1-4.0	60.0
	16.0	0.1-4.06	64.96
	16.8–17.0	0.1-3.75	63.75
	18.0–18.3	0.1-3.5	64.05
	19.0	0.1-3.42	64.98
	20.0	0.1-3.25	65.0
	21.0	0.1-3.0	63.0
	22.0	0.1-2.9	63.8
	22.5	0.1-2.89	65.025
	24.0	0.1-2.7	64.8
	25.2–25.5	0.1-2.5	63.75
	27.0	0.1-2.4	64.8
	28.0–29.0	0.1-2.1	60.9
	29.2–29.4	0.1-2.2	64.68
	30.0	0.1-2.0	60.0
	32.0	0.1-2.0	64.0
	33.0–34.0	0.1-1.9	64.6
	35.0–36.0	0.1-1.8	64.8
	36.5	0.1-1.75	63.875
	37.8	0.1-1.7	64.26
	38.0-43.0	0.1-1.5	64.5
	43.8–44.0	0.1-1.45	63.8
	45.0–46.2	0.1-1.4	64.68
	47.5–48.0	0.1-1.35	64.8
	50.4	0.1-1.25	63.0
	51.0–51.1	0.1-1.2	61.32
	54.6	0.1-1.15	62.79
	54.8–58.4	0.1-1.0	58.4
	58.8	0.1-1.1	64.68

Page 3 of 4







No. N8AUK 094747 0153 Rev. 00

Model	Rated output voltage (VDC)	Rated output current (A)	Maximum rated output power (W)
XSExxxyyyyzz, XSExxxyyyy, XSECxxxyyyyzz, XSECxxxyyyy	3.6–5.0	0.1-7.0	35.0
	5.1–9.0	0.1-6.5	58.5
	10.0-12.0	0.1-6.0	60.0
	12.1–12.6	0.1-5.0	63.0
	12.8–15.0	0.1-4.5	65.0
	16.0–20.0	0.1-3.75	65.0
	21.0–30.0	0.1-3.0	65.0
	31.0–58.8	0.1-2.0	65.0





