

접수번호:

KCA2023-08977

## 안 전 인 증 서 Safety Certificate

**안전인증번호**: HU10934-20005B

(Application No.)

제조업자/수입업자명: Xinsu Global Electronic Co., Limited

(Manufacturer/importer)

주 소: 3rd Floor, No.1 Building, C District, 108 Honghu Road, Yanluo Street, Bao'an District, 518127

(Address) Shenzhen, GuangDong, PEOPLE'S REPUBLIC OF CHINA.

제 품 명: 직류전원장치

(Product)

**기본모델명:** XSG2904200

(Basic Model)

**파생모델명** (Series Model):

XSG3403500,XSG4202500,XSG4202250, [이면기재]

정격/안전기준상의 모델구분: 100-240 V~, 50/60 Hz, 2.5 A (O/P: 29 Vdc, 4.2 A)

(Rating)

시험기준: K 60950-1(2011-12)

(Standard)

본 인증서는 제 조 국 명 : 중국

제조업자명: Xinsu Global Electronic Co., Limited

제조공장의 주소: 3rd Floor, No.1 Building, C District, 108 Honghu Road, Yanluo Street, Bao'an

District, 518127 Shenzhen, GuangDong, PEOPLE'S REPUBLIC OF CHINA.

의 제품에만 해당함

「전기용품 및 생활용품 안전관리법 시행규칙」제9조제2항, 제4항, 제10조제2항 또는 제15조제2항에 따라 안전인증서를 발급합니다. We issue this Safety Certificate for the above appliances in accordance with Article 9(2), 9(4), 10(2) or 15(2) of the Enforcement Rule of the Electrical Appliances and Consumer Products Safety Control Act.

2023 년 07 월 06 일 (Year) (Month) (Day)

## 한국기계전기전자시험연구 Korea Testing Certification Inst

※ 이 인증서는 「전기용품 및 생활용품 안전관리법」에 따른 제품의 안전성 확인에 한정된 것이며, 그 밖의 다른 법률이 적용되는 제품의 경우에는 해당 법률에 따라 추가로 인증 • 허가 등을 받아야 합니다.

첨부서류

- 1. 전기용품의 안전관리부품 및 재질목록(List of Critical Components)
- 2. 기본모델 파생모델의 내용(Description of the basic and series model)
- 3. 안전인증의 변경 현황(Revisions Status)

### <u>안전인증을 받은 자의 유의 사항</u> Notification for Recipients

본 증명서는 기재된 제조공장에서 생산된 제품으로서 적용된 안전기준에 적합한 경우에 한하여 유효합니다.

(This certificate is valid only when the product meets the safety standards and is produced from the manufacturing factory that states on this certificate.)

2. 안전인증 마크는 본래의 의미와 다르게 사용자가 오해를 일으킬 수 있는 방법으로 광고, 카탈로그등에 사용하면 인증정지 또는 취소의 사유가 됩니다.

(Cessation or cancellation of the certification may occur if the actual meaning of the Safety Certification Mark is misled to the public by false advertisement on a catalog of the product.)

3. 다음과 같은 사유가 발생할 경우에는 안전인증기관에 안전인증 변경 신청을 하여 안전인증서를 재교부 받아야 합니다.

(In case of the following events, the Safety Certificate shall be reapplied and reissued for revision)

1) 제조자, 대표자, 주소 등 인증서 기재내용의 변경

(Revisions in contents of the certificate such as manufacturer representative, address and etc.)

- 2) 파생모델의 추가, 변경 또는 삭제 (Additions, changes, or removals of series model)
- 3) 안전관리 부품의 변경 또는 추가

(Additions or changes in components which are listed on the certificate)

4. 안전인증을 받은 자는 다음 사항을 이행하여야 합니다.

(Recipients of the Safety Certificate shall comply with the followings.)

- 1) 안전인증 표시 등 인증요<mark>건의</mark> 유지관리
  - (Maintaining and preserving the Mark and other certification requirements)
- \* 안전인증을 받기 이전 또는 정지, 취소된 이후 생산된 제품에 안전인증 표시를 하면 법에 의거 처벌을 받게 됩니다

(It will be punished by the law if the certification mark is used before the issue (or after suspension or cancellation) of the certification.)

- 2) 자체 검사의 실시 및 그 기록관리 (Self-testing and record keeping)
- \* 안전인증을 받은 자는 제품검사를 철저히 실시하여 제품의 품질이 안전기준에 미달되지 않도록 유의. (Recipients of the Safety Certificate shall conduct products inspection strictly for products to comply with the safety standards)
- 5. 안전인증을 받을자는 전기용품 및 생활용품 안전관리법 제 7조에 따라 2년에 1회 정기검사를 실시하여야 한다. (Recipients of the Safety Certificate shall require to inspect once in two years according to the Article 7 section of the the Electrical Appliances and Consumer Products Safety Control Act.)
- 6. 인증서(증명서)에는 진위여부 확인을 위해 다음과 같은 사항이 적용되어 있습니다.
  - 1) 문서관리번호 (문서관리번호 노출시 CS홈페이지를 통해 기술문서 내용이 조회 가능함으로 사본 등 제출시 노출되지 않도록 주의하시기 바랍니다.)
  - 2) 시점확인필
  - 3) 2D바코드

#### 파생모델명

XSG4202000,XSG4201750,XSG4201500,XSG4201250,XSG4201000,XSG4200500,XSG 3363500,XSG3363000,XSG3362500,XSG3362000,XSG3361500,XSG3361000,XSG320 3500,XSG3203000,XSG3004000,XSG3003500,XSG2944000,XSG2943500,XSE294300 0,XSE2942500,XSG2924000,XSG2923500,XSE2923000,XSE2922500,XSG2904000,XS G2903500,XSE2903000,XSE2902500,XSG2804000,XSG2803500,XSG2524500,XSG25 24000,XSE2523000KR,XSG2405000,XSG2404500,XSG2404000,XSE2403500,XSE2403 000

KCA2023-08977

page: 1 / 8

안전인증번호: HU10934-20005B

(Certificate No) (Receipt No)

#### 1. 기본모델 · 파생모델의 내용 (General Descriptions of Certified Products)

1.1 제품의 설명 (Product description)

인증제품의 개요는 다음과 같다.

(Information on certified basic model product is as follow)

구 분(Section)	내 용 (Description)
용도 (Normal use)	The apparatus designed to be used for converting AC main voltage to DC low voltage.
내부구조 (Internal construction)	Consisting of the primary and reinforced or double insulated SELV circuit.
외부구조 (External construction)	Provided with plastic enclosure having min. V-1 flammability and appliance inlet.
기타(others)	Class II.

#### 1.2 전기용품의 표시 : 전기용품 및 생활용품 안전관리법 시행규칙 제20조(안전인증의 표시)에 따라 표시한다.

(Marking of KC Mark: Marking shall comply with the Article 20 of the Enforcement Rule of the Electrical Appliances and Consumer products Safety Control Act. )

#### 1.3 등록모델 (Registered Models)

구분 (Class)	모델명및정격 (Model / Rating)	기본모델과의 차이점 (Difference between basic model and series model)
기본모델 (Basic model)	XSG2904200 100-240 V~, 50/60 Hz, 2.5 A (O/P: 29 Vdc, 4.2 A)	
파생모델 (Variant model)	XSG3403500	Identical to the basic model except for the model designation, output rating (34 Vdc, 3.5 A)
	XSG4202500	Identical to the basic model except for the model designation, output rating (42 Vdc, 2.5 A)
8	XSG4202250	Identical to the basic model except for the model designation, output rating (42 Vdc, 2.25 A)
	XSG4202000	Identical to the basic model except for the model designation, output rating (42 Vdc, 2 A)

안전인증번호: HU10934-20005B

(Certificate No)

접수번호: KCA2023-08977

zeruncate No)		(Neceipt No)
	XSG4201750	Identical to the basic model except for the model designation, output rating (42 Vdc, 1.75 A)
	XSG4201500	Identical to the basic model except for the model designation, output rating (42 Vdc, 1.5 A)
	XSG4201250	Identical to the basic model except for the model designation, output rating (42 Vdc, 1.25 A)
5%	XSG4201000	Identical to the basic model except for the model designation, output rating (42 Vdc, 1 A)
3/2	XSG4200500	Identical to the basic model except for the model designation, output rating (42 Vdc, 0.5 A)
	XSG3363500	ldentical to the basic model except for the model designation, output rating (33.6 Vdc, 3.5 A)
	XSG3363000	Identical to the basic model except for the model designation, output rating (33.6 Vdc, 3 A)
	XSG3362500	Identical to the basic model except for the model designation, output rating (33.6 Vdc, 2.5 A)
50	XSG3362000	Identical to the basic model except for the model designation, output rating (33.6 Vdc, 2 A)
3/2	XSG3361500	Identical to the basic model except for the model designation, output rating (33.6 Vdc, 1.5 A)
	XSG3361000	Identical to the basic model except for the model designation, output rating (33.6 Vdc, 1 A)

page: 3 / 8

안전인증번호: HU10934-20005B

(Certificate No)

접수번호: KCA2023-08977

$\alpha$	$\sim$	
	XSG3203500	Identical to the basic model except for the model designation, output rating (32 Vdc, 3.5 A)
	XSG3203000	Identical to the basic model except for the model designation, output rating (32 Vdc, 3 A)
	XSG3004000	Identical to the basic model except for the model designation, output rating (30 Vdc, 4 A)
50	XSG3003500	Identical to the basic model except for the model designation, output rating (30 Vdc, 3.5 A)
3/2	XSG2944000	Identical to the basic model except for the model designation, output rating (29.4 Vdc, 4 A)
	XSG2943500	Identical to the basic model except for the model designation, output rating (29.4 Vdc, 3.5 A)
	XSE2943000	Identical to the basic model except for the model designation, output rating (29.4 Vdc, 3 A)
	XSE2942500	Identical to the basic model except for the model designation, output rating (29.4 Vdc, 2.5 A)
56	XSG2924000	Identical to the basic model except for the model designation, output rating (29.2 Vdc, 4 A)
3%	XSG2923500	Identical to the basic model except for the model designation, output rating (29.2 Vdc, 3.5 A)
	XSE2923000	Identical to the basic model except for the model designation, output rating (29.2 Vdc, 3 A)

## 기 술 문 서 Technical Document page: 4 / 8

안전인증번호: HU10934-20005B

(Certificate No)

접수번호: KCA2023-08977

ter uncate (NO)		(Receipt No)
	XSE2922500	Identical to the basic model except for the model designation, output rating (29.2 Vdc, 2.5 A)
	XSG2904000	Identical to the basic model except for the model designation, output rating (29 Vdc, 4 A)
	XSG2903500	Identical to the basic model except for the model designation, output rating (29 Vdc, 3.5 A)
5%	XSE2903000	Identical to the basic model except for the model designation, output rating (29 Vdc, 3 A)
3/2	XSE2902500	Identical to the basic model except for the model designation, output rating (29 Vdc, 2.5 A)
	XSG2804000	Identical to the basic model except for the model designation, output rating (28 Vdc, 4 A)
	XSG2803500	Identical to the basic model except for the model designation, output rating (28 Vdc, 3.5 A)
	XSG2524500	Identical to the basic model except for the model designation, output rating (25.2 Vdc, 4.5 A)
10	XSG2524000	Identical to the basic model except for the model designation, output rating (25.2 Vdc, 4 A)
3/2	XSE2523000KR	Identical to the basic model except for the model designation, output rating (25.2 Vdc, 3 A)
	XSG2405000	Identical to the basic model except for the model designation, output rating (24 Vdc, 5 A)

page: 5 / 8

안전인증번호: HU10934-20005B

(Certificate No)

접수번호: KCA2023-08977

(Receipt No)

90	XSG2404500	Identical to the basic model except for the model designation, output rating (24 Vdc, 4.5 A)
	XSG2404000	Identical to the basic model except for the model designation, output rating (24 Vdc, 4 A)
	XSE2403500	Identical to the basic model except for the model designation, output rating (24 Vdc, 3.5 A)
5%	XSE2403000	Identical to the basic model except for the model designation, output rating (24 Vdc, 3 A)

#### 2. 안전관리 부품 및 재질목록(List of Critical Components)

부품명(회로기호) Components(Part no.)	제조자(상표명) Manufacturer(Brand)	모델명(형식) Model(Type)	정격 또는 특성 (Technical Data)	인증규격 (Certification)
Enclosure	TEIJIN LIMITED RESIN AND PLASTIC	LN-1250G(#)(*)	V-0,min. thickness: 1.5 mm, 115 ℃	UL
Enclosure (Alt)	SABIC INNOVATIVE PLASTICS US L L C	940(f1)	V-0,min. thickness: 1.5 mm, 120 ℃	UL
Enclosure (Alt)	SABIC INNOVATIVE PLASTICS B V	LTA6020(f1)	V-0,min. thickness: 1.5 mm, 125 ℃	UL
Enclosure (Alt)	TRINSEO(HONG KONG) LTD	EMERGE PC 8600(a)	V-0,min. thickness: 1.5 mm, 125 ℃	UL
Appliance Inlet (CON1)	Zhe Jiang BeiEr Jia Electronic Co., Ltd.	ST-A03-005	2.5 A, 250 Vac	KC
Appliance Inlet (CON1) (Alt)	Yueqing Leci Electronics Co., Ltd.	DB-8	2.5 A, 250 Vac	KC
PCB	KINGBOARD LAMINATES HOLDINGS LTD	KB-2150	105°C, V-0	UL
PCB (Alt)	SHANDONG JINBAO TECH-INNOV CORPORATION	ZD-90F, ZD-90FS	130°C, V-0	UL

page: 6 / 8

안전인증번호: HU10934-20005B

접수번호: KCA2023-08977

(Certificate No)

er uncate 110)			(Neceipt No)	
부품명(회로기호) Components(Part no.)	제조자(상표명) Manufacturer(Brand)	모델명(형식) Model(Type)	정격 또는 특성 (Technical Data)	인증규격 (Certification)
PCB (Alt)	SHUNDE JUN'AN SHENGSHENG ELECTRONIC CO LTD	S-1D	130°C, V-0	UL
PCB (Alt)	Interchangeable	Interchangeable	130°C, V-0	UL
Fuse (F1)	Dongguan Anlu Electronics Technology Co., Ltd.	AMT T3.15A 250V	T3.15A, 250VAC	KC
Fuse (F1) (Alt)	Shenzhen Lanson Electronics Co.Ltd.	SMT T3.15A 250V	T3.15A, 250VAC	KC
Fuse (F1) (Alt)	Dongguan Walter Electric Co., Ltd.	2010 3.15A 250V	T3.15A, 250VAC	KC
X-Capacitor (CX1)	Shenzhen Yixingjie Capacitors Co., Ltd.	MKP	0.47 uF, min.310 Vac, X2	KC
X-Capacitor (CX1) (Alt)	Shantou High- New Technology Dev. Zone Songtian Enterprise Co., Ltd.	MPX	0.47 uF, min.310 Vac, X2	KC
Bleeder resistor (R1, R2, R1A, R2A)	Interchangeable	Interchangeable	1.5 №	-
Y-Capacitor (CY1)	Xiangtai Electronics (Shenzhen) Co., Ltd.	YO E 2200pF	Max. 2200pF, Min. 400Vac, Y1	KC
Y-Capacitor (CY1) (Alt)	Dongguan City Dafu Electronics Co., Ltd.	CT7 Y1 Series	Max. 2200pF, Min. 250Vac, Y1	КС
Y-Capacitor (CY1) (Alt)	Guangdong South Hongming Electronic Science and Technology Co.Ltd.	Y1, 250Vac	Max. 2200pF, Min. 250Vac, Y1	KC
Y-Capacitor (CY4, CY5)	Xiangtai Electronics (Shenzhen) Co., Ltd.	YO B 470pF	Max. 470pF, Min. 400Vac, Y1	KC
Y-Capacitor (CY4, CY5)	Dongguan City Dafu Electronics Co., Ltd.	CT7 Y1 Series	Max. 470pF, Min. 250Vac, Y1	KC
Y-Capacitor (CY4, CY5)	Guangdong South Hongming Electronic Science and Technology Co.Ltd.	Y1, 250Vac	Max. 470pF, Min. 250Vac, Y1	KC

page: 7 / 8

안전인증번호: HU10934-20005B

접수번호: KCA2023-08977

(Certificate No)

(Receipt No)

부품명(회로기호) Components(Part no.)	제조자(상표명) Manufacturer(Brand)	모델명(형식) Model(Type)	정격 또는 특성 (Technical Data)	인증규격 (Certification)
Y-Capacitor (CY9, CY10)	Xiangtai Electronics (Shenzhen) Co., Ltd.	YO B 470pF	Max. 470pF, Min. 400Vac, Y1	KC
Y-Capacitor (CY9, CY10)	Dongguan City Dafu Electronics Co., Ltd.	CT7 Y1 Series	Max. 470pF, Min. 250Vac, Y1	KC
Y-Capacitor (CY9, CY10)	Guangdong South Hongming Electronic Science and Technology Co.Ltd.	Y1, 250Vac	Max. 470pF, Min. 250Vac, Y1	KC
Opto-coupler (U2)	EVERLIGHT ELECTRONICS CO LTD	EL817	Dti $\geq$ 0.4 mm, ext. dcr $\geq$ 7.6 mm, ext. dcr $\geq$ 7.6 mm	VDE
Opto-coupler (U2) (Alt)	BRIGHT LED ELECTRONICS CORP	BPC 817	Dti $\geq$ 0.4 mm, ext. dcr $\geq$ 7.6 mm, ext. dcr $\geq$ 7.6 mm	VDE
Opto-coupler (U2) (Alt)	SHENZHEN ORIENT COMPONENTS CO LTD	ORPC-817	Dti $\geq$ 0.4 mm, ext. dcr $\geq$ 7.6 mm, ext. dcr $\geq$ 7.6 mm	VDE
Opto-coupler (U2) (Alt)	Sharp Corporation Electronic Components and Devices Division	PC817	Dti≥ 0.4 mm, ext. dcr ≥ 6.4 mm, ext. dcr≥ 6.4 mm	VDE
Line Choke (FL1)	SHENZHEN XINDAHUI ELECTRONICS CO., LTD	EF20	10mH, 130°C	-
Line Choke (L1)	SHENZHEN CHENG YEXIN ELECTRONIC TECHNOLOGY CO., LTD	T60-26	40uH, 130°C	
Transformer (T1)	SHENZHEN XINDAHUI ELECTRONICS CO., LTD.	TR-120-T2	Class B	-

#### 3. 전기용품안전인증의 변경현황(Status of Certificate Revisions)

0171/0-4-)	발급현황(Status of issues)
일자(Date)	변경내용(Modification of Contents)

page: 8 / 8

안전인증번호: HU10934-20005B 접수번호: KCA2023-08977

(Certificate No) (Receipt No)

90	기본+파생모델등록(Basic + Series Model)
2020/01/02	
	주소(제조자)
2023/07/06	

#### 4. 기타(Carefully Informed Note)

1) 안전관리부품 및 재질목록에 기재된 사항은 안전에 직접적인 영향을 주는 부분이므로 내용을 변경 또는 복수등재를 원하는 경우 안전인증변경신청 또는 안전확인변경신고를 하여야 합니다. 안전인증변경신청 또는 안전확인변경신고를 하지 않고 임의로 변경하는 경우에는 전기용품 및 생활용품 안전관리법에 따라 행정조치 될수 있습니다.

The certificate holder should apply for a revision of the certificate if the registered critical components are to be changed, modified or alternated. Should the contents of Certificate are altered without the application for the modification, the administrative measures can occur according to the Electrical Appliances and Consumer Products Safety Control Act.

2) 정기검사(시료채취포함)를 거부, 방해 또는 기피하는 경우에는 전기용품 및 생활용품 안전관리법 제 11조에 따라 안전인증이 취소될수 있습니다.

If Follow-up Factory Inspection, including sampling representative model by 11 categories of the certified product at factory-site for re-testing, should not has been arranged by Certificate holder, Safety Certification(KC Mark) may be withdrawn according to the Article 11 of the Electrical Appliances and Consumer Products Safety Control Act.

3) 공장주소(전화번호포함), 대표자, 상호 및 부품변경, 신고인정보 등 안전인증 또는 안전확인신고의 내용이 변경되었을 때, 안전인증변경신청 또는 안전확인변경신고를 하지 않을 경우에는 전기용품 및 생활용품 안전관리법에 따라 행정조치 될 수 있습니다.

Should a factory address, president name, manufacturer name and critical component are altered without the application for the modification, the administrative measures can occur according to the Electrical Appliances and Customer Products Safety Control Act.

4) 조건부 인증사항 (Conditional certification items):